# SL-1210GEG-K Technics



Categorie: Platenspeler
Merk: Technics
Model: SL-1210GEG-K

5025232923182

4.499,00€

## OMSCHRIJVING

**Coreless Direct Drive Motor**

Conventional analogue turntables have problems with degradation in sound quality caused by factors such as minute speed vibration during rotation and rotation irregularity called “cogging.” In the SL-1200G, the use of a newly developed coreless direct-drive motor with no iron core eliminates cogging. Also, the twin-rotor construction reduces the bearing load while maintaining high torque and also reduces minute vibration during rotation. These factors enable reproduction of the warm, exquisitely detailed sound etched on analogue records.

**High-precision Motor Control Technology**

The application of motor control technology developed for Blu-ray devices and switching the drive mode depending on the operational status of the motor achieve a high-starting torque and highspeed stability.

**Three-layered Turntable Platter**

The turntable has a three-layered construction with a rigidly combined brass and aluminium die-cast platter.

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

With a deadening rubber covering its entire rear surface to eliminate unnecessary resonance, thereby achieving high rigidity and vibration damping. This delivers smooth rotational stability and inertial mass surpassing the SP-10MK2, the direct-drive turntable standard used by broadcast stations worldwide, as well as having more than twice the inertial mass of the SL-1200MK5.

**High-level Balance Adjustment**

When the weight distribution of the turntable is uneven, excess vibration or noise occurs during rotation, which causes degradation in sound quality. Therefore, the balance of the turntable is adjusted at the factory by using specialized high-precision balance adjustment equipment for each and every item after the turntable is assembled. Turntables that have undergone adjustment are labelled with a sticker reading “BALANCED” to indicate that adjustment has been done.

**High-sensitive Tonearm**

The tonearm employs lightweight magnesium which has a high damping effect, with cold drawing improving the characteristics of the material and achieving the high-precision required. In addition, high initial-motion sensitivity is attained by employing the traditional Technics gimbal suspension construction with horizontal rotation axis and the vertical rotation axis intersecting at a single central point, as well as high-precision bearings using a cut-processed housing.

**Four-layered Cabinet Construction**

A hairline-processed, 10-mm-thick top panel of immaculate aluminium has been added to the previous three-layered construction of aluminium die-cast, BMC, and heavyweight-class rubber on the SL-1200MK5. This four-layered construction combines high rigidity with a high-quality finish and feel.

**High-quality Terminals**

The use of brass-milled, gold-plated phono terminals and ground terminals prevent degradation in sound quality while enabling the easy attaching and detaching of cables. Also the use of metal shielding construction inside the case reduces the effects of external noise.

## SPECIFICATIE

| Algemeen | | Fysieke kenmerken | |
|---|---|---|---|
| Toerental | 33 rpm, 45 rpm, 78 | Breedte | 45.3 cm |

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

| | | | |
|---|---|---|---|
| platenspeler | rpm | Diepte | 37.2 cm |
| | | Gewicht | 18 g |
| | | Hoogte | 17 cm |
| | | Kleur | Zwart |

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

| **Van Havere TV, Hifi & Home Automation Loewe Gallery, Bang & Olufsen Kapellen, Domotica** | **Bang & Olufsen Antwerpen, Loewe Gallery Antwerpen** | **Van Havere IT & Telecom, Cyberdrome** |
|---|---|---|
| Hoevensebaan 99 | Riemstraat 22B | Eikendreef 5a |
| Parking Essenhoutstraat 52 | | Parking Essenhoutstraat 52 |
| BE 2950 Kapellen | BE 2000 Antwerpen | BE 2950 Kapellen |
| Tel: 03 664 75 68 | Tel: 03 288 91 08 | Tel: 03 605 07 60 |